

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>30 SEP 2008</b>		2. REPORT TYPE <b>Annual</b>		3. DATES COVERED <b>00-00-2008 to 00-00-2008</b>	
4. TITLE AND SUBTITLE <b>A Chiometer And A New Winch For SWIMS3</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>University of Washington,Applied Physics Laboratory,1013 NE 40th St.,Seattle,WA,98105-6698</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>code 1 only</b>					
14. ABSTRACT <b>Our goal is to understand mixing in shallow water, i.e., the upper 500 to 1000 m, by observing it in relation to the larger-scale processes producing it. Regimes of interest include open-ocean fronts, continental slopes and shelves, ridges and canyons.</b>					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Same as Report (SAR)</b>	18. NUMBER OF PAGES <b>2</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

## **A Chiometer and a New Winch for SWIMS3**

Michael C. Gregg and Jack B. Miller  
Applied Physics Laboratory, University of Washington  
1013 NE 40<sup>th</sup> St.  
Seattle, WA 98105-6698  
Phone: 206-543-1353 (Gregg), 206-543-9959, Fax: 206-543-6785  
Email: [gregg@apl.washington.edu](mailto:gregg@apl.washington.edu), [miller@apl.washington.edu](mailto:miller@apl.washington.edu)

Grant # N00014-07-1-0929

### **LONG-TERM GOALS**

Our goal is to understand mixing in shallow water, i.e., the upper 500 to 1000 m, by observing it in relation to the larger-scale processes producing it. Regimes of interest include open-ocean fronts, continental slopes and shelves, ridges and canyons.

### **OBJECTIVES**

This project will add a chiometer to SWIMS3, our depth-cycling towed body, to observe scalar microstructure in addition to the larger-scale variables currently measured. It will also replace the winch used to cycle SWIMS3 in depth.

### **APPROACH**

Owing to its faster speed and tighter profiles, SWIMS3 can sample mixing processes much more intensively than can microstructure profilers. We have been estimating dissipation rates using Ozmidov scaling of density overturns. Adding the Chiometer will provide a more direct measure by adding the variance of small-scale scalar gradients to the data suite.

The new winch is needed simply to replace the present one, which we have used since 1993. Because it will carry longer and thicker tow line, it will let us profile deeper and reduce the chance of losing SWIM3 by cable failure.

### **WORK COMPLETED**

Firmware for Chiometer data acquisition has been written, and all pieces have been built. We, however, hit a snag when a prototype analog-to-digital unit was too noisy to be useful. To obtain 18-bit conversion at high speeds requires building an A/D board from scratch; no suitable conversion modules are available. Fortunately, a new commercial A/D prototype board proved successful, and our board is now being built to mimic it. We still expect to provide a working unit to Craig Lee for use on Triaxus next February in the Philippines.

After nearly losing SWIMS3 in the Philippines earlier this year, when it apparently snagged a sunken Fish Aggregation Device (FAD), we went through a lengthy redesign effort to increase the diameter of

the cable to be used with the new winch, which had not been ordered. Now ordered, the new winch should be delivered early next year.

## **RESULTS**

No results have been obtained yet.

## **IMPACT/APPLICATIONS**

The Chiometer is expected to be ready for Craig Lee to use during PHILEX09. Shortly afterward, we will use it in Monterey Canyon on an NSF.